

Unit: mm

## INSPECTION

## WIDE RANGE THREE POINTS INTERNAL MICROMETERS

- Meet DIN863-4
- Graduation 0.001mm
- Carbide measuring faces
- Ratchet stop
- Setting rings are included (except 200-300mm)



<sup>\*</sup>Supplied with manufacturer inspection certificate



3228-70









## DIGITAL WIDE RANGE THREE POINTS INTERNAL MICROMETERS



- Meet DIN863-4
- Resolution 0.001mm/0.00005" (resolution of 3128-300 is 0.001mm/0.0001")
- ÎP54 dust/waterproof
- Buttons: on/off, set, mm/inch
- Data output
- Automatic power off
- Carbide measuring faces
- Ratchet stop
- Supplied with extension rods
- Setting rings are included (except 200-300mm)
- Optional accessory:
  wireless transmitter code 7315-30 (receiver is needed) page 5, bluetooth transmitter code 7214-30 page 11, data output cable code 7302-30 page 20





Code	Range	Accuracy	Setting ring	Extension rod (included)
3128-70*	50-70mm/1.97-2.76"	5µm	Ø50mm (included)	150mm
3128-100*	70-100mm/2.76-3.94"	5µm	Ø70mm (included)	150mm
3128-150*	100-150mm/3.94-5.91"	6µm	Ø100mm (included)	150mm
3128-250*	150-250mm/5.91-9.84"	8µm	Ø150mm (included)	150mm
3128-300*	200-300mm/7.87-11.81"	9µm	Ø200mm (optional)	150mm

<sup>\*</sup>Supplied with manufacturer inspection certificate




extension rod (included)

210

## DIGITAL WIDE RANGE THREE POINTS INTERNAL MICROMETER









50mm replaceable measuring jaws (included)

7




100mm replaceable measuring jaws (included)






3621-500

- Resolution 0.001mm/0.0001" (resolution is 0.00005" when <10")
- Replaceable measuring jaws, wide measuring range
- Buttons: on/off, set, mm/inch
- Data output
- Automatic power off
- Carbide measuring faces
- Ratchet stop
- Supplied with extension rods
- Optional accessary: setting rings (code 6312-200, 6312-300, 6312-400), wireless transmitter code 7315-30 (receiver is needed) page 5, bluetooth transmitter code 7214-30 page 11, data output cable code 7302-30 page 20





Code	Range	Accuracy	Measuring jaws (included)	Extension rods H (included)
3621-500	200-500mm/7.87-19.69"	(1+L/50) μm*	50mm (3pcs), 100mm (3pcs)	150mm, 500mm

<sup>\*</sup>L=maximum measuring diameter (mm)