


## **TRY SQUARE**

- Graduation: 1mm
- Stainless steel blade, aluminum base

| Code     | Size (LxW)  | Squareness             |       |  |
|----------|-------------|------------------------|-------|--|
| Code     | Size (LXVV) | Inside (α) Outside (β) |       |  |
| 2275-300 | 300x170mm   | 0.5mm                  | 0.5mm |  |




#### **TRY SQUARE**

- Graduation: 1mm
- Aluminum blade and base
- 4 milled surfaces

13

- Retractable metal ledge support
  Etchings and holes for beveling and framing: 10°, 15°, 22.5°, 30°, 45°, 50° and 60°
  Etchings and holes every cm for fluid pencil marking





| Codo     | Sizo (LvM) | Squareness |             |  |  |
|----------|------------|------------|-------------|--|--|
| Code     | Size (LxW) | Inside (α) | Outside (β) |  |  |
| 2280-300 | 300x150mm  | 0.5mm      | 0.5mm       |  |  |

### **ADJUSTABLE SQUARE**


- The straight edge can move and can be locked by the clamping screw
- Made of hardened stainless steel





| Code   | Squareness (a, b, c, d) |
|--------|-------------------------|
| 4701-1 | 7µm                     |








## 45° SQUARES

■ Made of hardened stainless steel

(mm) **Accuracy** Code Size (LxW) C D Inside (α) Outside (β) 4745-1100 100x70mm  $27 \mu m$  $30 \mu m$ 20 20 5 4745-1120 120x80mm 29µm 32µm 20 20 5 4745-1150 150x100mm  $32 \mu m$ 35µm 20 20 5 4745-1200 200x130mm 25 25 5 36µm  $40 \mu m$ 




#### 45° SQUARES WITH WIDE BASE

■ Made of hardened stainless steel

(mm)

| Code Size (LxW) |               | Accuracy   |             | С  | D   | н | Е  |
|-----------------|---------------|------------|-------------|----|-----|---|----|
| Code            | e Size (LXVV) | Inside (α) | Outside (β) | C  | , D | " | -  |
| 4747-100        | 100x70mm      | 27µm       | 30µm        | 20 | 20  | 5 | 20 |
| 4747-120        | 120x80mm      | 29µm       | 32µm        | 20 | 20  | 5 | 20 |
| 4747-150        | 150x100mm     | 32µm       | 35µm        | 20 | 20  | 5 | 20 |
| 4747-200        | 200x130mm     | 36µm       | 40µm        | 25 | 25  | 5 | 25 |





**60° SQUARES** 


Made of hardened stainless steel

(mm)

| Code Size (LxW) |             | Acc        | С           | D  | н  |   |
|-----------------|-------------|------------|-------------|----|----|---|
| Code            | Size (LXVV) | Inside (α) | Outside (β) | U  | ע  | п |
| 4760-1120       | 120x80mm    | 30µm       | 32µm        | 20 | 20 | 5 |
| 4760-1150       | 150x100mm   | 32µm       | 35µm        | 20 | 20 | 5 |
| 4760-1200       | 200x130mm   | 37µm       | 40µm        | 25 | 25 | 5 |








### 60° SQUARES WITH WIDE BASE

■ Made of hardened stainless steel

|          |             |            |             |    |    | ( | (mm) |
|----------|-------------|------------|-------------|----|----|---|------|
| Code     | Cina (LyAA) | Accuracy   |             | _  | D  | н | Е    |
| Code     | Size (LxW)  | Inside (α) | Outside (β) | ٦  | ט  |   | -    |
| 4762-120 | 120x80mm    | 30µm       | 33µm        | 20 | 20 | 5 | 20   |
| 4762-150 | 150x100mm   | 33µm       | 36µm        | 20 | 20 | 5 | 20   |
| 4762-200 | 200x130mm   | 37µm       | 41µm        | 25 | 25 | 5 | 25   |



4762-120







# **COMBINATION SQUARE (ECONOMIC TYPE)**

- Square head (made of zinc): set the blade at 90° or 45° to an edge of a workpiece accuracy: ±0.5°
- Blade (made of stainless steel): range: 300mm/12", graduation: 1mm and 1/32" on front face,1mm and 1/16" on back face











Code 2276-300

# **COMBINATION SQUARE SET (OPEN TYPE PROTRACTOR)**





- Center head (made of cast iron): to locate center of cylinders with diameter (Ød): 30-100mm accuracy: ±0.15mm
- Protractor head (made of cast iron): set the blade at desired angle to an edge of a workpiece, and can be used to measure angles range: 0-180°
- accuracy: ±20min


  Square head (made of cast iron):
  set the blade at 90° or 45° to an edge of a workpiece
  accuracy: ±8min for 90° square,
- ±10min for 45° square

  Blade (made of stainless steel):
  range: 300mm/12",
  graduation: 0.5mm and 1/32" on front face,

graduation: 0.5mm and 1/32" on front face 1mm and 1/64" on back face

■ Optional accessory: rigid ruler (code **7113**)

| Code   | Remark      |
|--------|-------------|
| 2274-4 | 4-piece set |



15